

SIMATIC DP, RS485 REPEATER FOR THE CONNECTION OF PROFIBUS/MPI BUS SYSTEMS WITH MAX. 31 NODES; MAX. 12 MBIT/S, DEGREE OF PROTECTION IP20 IMPROVED USABILITY



Supply voltage

Rated value (DC)	Yes
<ul style="list-style-type: none"> • 24 V DC 	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

Input current

Current consumption, max.	100 mA; 100 mA without loads at PG/OP socket; 130 mA load at PG/OP socket (5 V/90 mA); 200 mA load at PG/OP socket (24 V/100 mA)
---------------------------	--

Interfaces

PROFIBUS DP	
<ul style="list-style-type: none"> • Transmission rate, max. 	12 Mbit/s; 9.6 kbit/s to 12 Mbit/s

Degree and class of protection

Degree of protection acc. to EN 60529	Yes
<ul style="list-style-type: none"> • IP20 	

Ambient conditions

Ambient temperature during operation	
--------------------------------------	--

• min.	0 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Relative humidity	
• Operation, max.	95 %; at 25 °C
Connection method	
Bus cables	2 terminal blocks
Power supply	Terminal block
Dimensions	
Width	45 mm
Height	128 mm
Depth	67 mm
Weights	
Weight, approx.	350 g
last modified:	29.07.2015